

Product Name

# COOLING WORKING TABLES CFI-TCP 30



## Purpose:

The TPC 30 are refrigerated working tables, with static positive refrigeration, designed to receive 400x600mm trays or grids. They exist in built-in refrigerating unit version (GL) and in remote refrigerating unit version (GD).

## Features:

- All the internal angles are rounded off to ensure a perfect cleaning.
- All the supports are removable without any tools.
- Panels insulated with polyurethane foam 42kg /m<sup>3</sup>, high pressure.
- 400x600 trays or grids must be ordered separately.
- Built-in refrigerating unit H.T.A. (High Ambient Temperature, +43°C maximum).
- Evaporation tray for the defrosting waters (removable).
- Batteries protected by a reinforced cataphoresis treatment.
- The TPC range can be entirely disassembled. Full stainless steel panels or PVC coated.

## Specification

Size of supports	400 x 600	Fluid	R448A
Support entry direction	400	Voltage	220-240V~IPH+N+T
Number of supports per level	1	Frequency	50/60 Hz
Total number of supports	33	Connecting electrical power	0,52 kW
Number of doors	3	Connection	4 A
Number of levels	11 per door	Stainless steel top (1700x885)	paying option
Spacing out of levels	50 mm	Stainless steel back guard (1700)	paying option
Adjustable every	50 mm	Granite top (1700x885)	paying option
Level depth	600	Granite back guard 20mm thick (1700)	paying option
Refrigerating unit	1/3 CV	Packing (LxPxH)	2350 x 1010 x 1090 mm
Refrigerating capacity at -15°C	0,6 kW		Net weight 250 kg